

INTRODUCING

RUBBERLOC

Conveyor Belt Repair

“REDUCES CONVEYOR DOWNTIME”

Rubberloc cures within one hour no matter the thickness of the conveyor belt



www.seconveyors.com.au

RubberLoc - Conveyor belt repair system is specifically formulated for rapid cure time and aggressive adhesion. Excellent abrasion re-sistance allows for long-lasting repairs, giving dramatic increases to conveyor belt service life.

Features and Benefits:

Reduces conveyor downtime - Rubberloc cures within one hour no matter the thickness of the conveyor belt.

- Thus the belt can be restarted 1 hour after application
- Superior adhesion compared to our competitors.
- Permanent repair system not a temporary patch.
- 400% Elasticity - The product does not crystallize and therefore does not crack or peel
- 18 months of storage
- Made in USA Specifications:
- Hardness (cured) Shore A – 76-85
- Tensile Strength 6895 PSI
- Elongation 417%
- 100% Modulus 1176 PSI
- Tear Strength D470-PLI 142
- Tear Strength DIECV-PLI
- Acid resistance 5%

Rubberloc kit Includes:

- Cleaner
- Primer
- 2-part polymer 750 grams
- Rubber gloves
- Can opener
- Mixing stock
- Application brush and trowel
- Application instructions
- Safety information

Applications:

- Rubberloc maintains its physical and chemical properties when applied on:
- Rubber
- Metal
- Concrete
- Wood

RUBBERLOC IS A PERMANENT SOLUTION

For more information

Head Office

299 Commercial Street West
Mount Gambier, SA 5291
08 8723 3333

Adelaide Office

13 Edison Drive
Golden Grove, SA 5125
08 8251 3204